MR F75-D



CLASS-D FIXED MOUNT VHF RADIO

The latest in Class-D Digital Selective Calling (DSC) Technology.

Handheld speaker/microphone Loud and clear communication with unique handheld speaker/microphone.

Large LCD screen Large and bright LCD screen for easy viewing.

SubmersibleDesigned to JIS7 standards.

All NOAA weather channels Instant access to national All Hazards and weather information, 24 hours a day.





Features Benefits

Compliant with the latest FCC specifications for Class-D VHF Radios. Digital Selective Calling allows you to send a distress signal at the touch of a button or exchange position information with other boats or stations. DSC features on this Class-D radio include; A Dedicated Channel 70 (DSC Channel) Receiver, GPS Position Display Capability, Illuminated Distress Button, Easy MMSI Entry, Position Send and Request, Position Input Reminder, Coast Guard DSC Check Capability, etc.
Dual output power for short and long communication.
Allows operation on any of the three (3) different channel maps established for these areas.
Instant access to national all hazards and weather information, 24 hours a day.
Alerts with an audible tone and visual alarm if threatening weather is nearby.
Instant access to channel 16 and channel 9 for emergency situations.
When connected to a Cobra or most other GPS receivers, you can send your position to other boats in an emergency, or exchange position information with other boats or stations.
Monitors three (3) channels at once – Channel 16, Channel 9 and one (1) user selected channel.
Scan channels programmed in memory to find conversations in progress.
Shows the strength of incoming signal.
Allows high visibility of function keys.
See radio settings from practically anywhere with the largest LCD available on a fixed radio.
Blocks background noise and allows listening to radio signals on the speaker/microphone. Controls allow instant access to channels 16 & 9, speaker/microphone volume control and changing of channels & setting features.
Allows connection of an external speaker (not included).
Allows calling other boats over a PA speaker (not included).
Meets JIS7 standards; Submersible for 30 minutes in one meter deep water.
For products sold in the U.S.A.

Included Accessories

Flush Mount Kit & Surface Mount Kit	Easy installation of radio in or on almost any flat surface with supplied hardware.			
GPS Interface Cab	Allows connection of a GPS receiver.			



Cobra®, CobraMarine®, Nothing Comes Close to a Cobra®, and the snake design are registered trademarks of Cobra Electronics Corporation, USA. Cobra Electronics Corporation™ is a trademark of Cobra Electronics Corporation, USA.

©2010 Cobra Electronics Corporation, 6500 West Cortland Street, Chicago, IL 60707, USA

Unit Specifications General

Number of Channels	All: U.S.A., Canadian, International 10 NOAA Weather Channels
Channel Spacing	25 kHZ
Modulation	5 kHz Max.
Input Voltage	13.8 VDC
Current Drain: Stand-by	200 mA
Receive	300 mA
Transmit	5 A @ High Power 1 A @ Low Power
Temperature Range	-20°C to 60°C
Unit Dimensions	6.25" x 2.25" x 7.125" (159 mm x 57 mm x 180 mm)
Unit Weight (Lbs)	2 lbs., 6.8 oz. (1100 g)

Receiver

Frequency Range	156.050 to 163.275 MHz
Receiver Type	Double Conversion Super-Heterodyne
Sensitivity: 20 dB Quieting	0.35 uV
12 dB Sinad	0.30 uV
AF Output	4 Watts @ 8 Ohms

Transmitter

Frequency Range	156.025 to 157.425 MHz
RF Output Power	1 or 25 Watts
Spurious Emissions	-60 dB @ High Power -55 dB @ Low Power
Microphone Type	Electret
Microphone Impedance	2000 Ohms
Frequency Stability	+/-10 ppm
FM Hum & Noise	40 dB

Packaging Specifications

Individual Clam/Box Dimensions	12.21" x 9.25" x 2.95" (310 mm x 236 mm x 75 mm)
Individual Clam/Box Weight	2 lbs., 13.3 oz. (1284 g)
Master Pack Qty.	4
Master Pack Dimensions	13.27" x 10.04" x 13.31" (337 mm x 255 mm x 338 mm)
Master Pack Weight	12 lbs., 7.5 oz. (5662 kg)
SKU # (White)	MR F75-D
UPC #	0 28377 20151 6
Master Pack Barcode	1 0028377 20151 3
SKU # (Black)	MR F75B-D
UPC #	0 28377 20152 3
Master Pack Barcode	1 0028377 20152 0

Specifications subject to change without notice.



1.77"

45.00mm





Distress

